

## Addressable Weather Proof Manual Call Point

Model - AA103WCP

### Overview:

This addressable device is intended to be used for manually operated fire alarm system. Enclosure of this unit is designed to sustain with weather protection, it can be used at open areas where it gets direct sunlight, rain. This addressable device has push button switch for signalling fire warning system. The unit supplied along with hammer and chain. When anyone notices fire, they can just activate this unit by breaking the glass. This device being addressable, the system can automatically indicate the location at display of panel monitor, as well as to trigger appropriate speakers/sounders to alert/evacuate and leaving other areas undisturbed.



### Example indication on detection of fire



### CONTROL PANEL

# DATA SHEET

Addressable Weather Proof Manual Call Point  
Model - AA103WCP



## Electrical specifications

Operating voltage	18-24V DC
Quiescent current	200 $\mu$ A
Alarm current	1mA(max)

## General specifications

Operating temperature	-10°C to 55°C
Storage temperature	-10°C to 60°C
Humidity	0-95% RH (Non-condensing)
Wiring	2 core
Area classification	Safe area
Type of protection	Weatherproof-Wp
Apparatus standard	IS-13947/93
Gas Groups	Group 1,2A, 2B
CMRI Certificate No.	CMRS/TC/H167
Approvals	CCE

## Indications

Normal indicator	Green LED (Blinks 50+/-10 sec)
Alarm indicator	Red LED (Glows steady)